









































































<p>Reset to Factory Default</p>  <p>M_DEFAULT</p>	 <p>1</p>	 <p>6</p>
<p>Enable RS232 Communication</p>  <p>RS232 Serial</p>	 <p>9</p>	 <p>FIN (Finish)</p>
 <p>PROGRAM Baud Rate (BPS)</p>	 <p>4</p>	 <p>END (Exit)</p>
 <p>PROGRAM Baud Rate (BPS)</p>	 <p>6</p>	 <p>PROGRAM</p>
 <p>4 (2400)</p>	 <p>FIN (Finish)</p>	<p>Change Code39 to * Symbol ID : 1 character</p> 
<p>Data Frame</p> 	<p>Formatter Control</p> 	 <p>0</p>
 <p>7 (7,E,1)</p>	 <p>0</p>	 <p>6</p>
 <p>END (Exit)</p>	 <p>5</p>	 <p>2</p>
 <p>PROGRAM</p>	 <p>FIN (Finish)</p>	 <p>A</p>
<p>Symbology ID Transmission</p> 	 <p>PROGRAM</p>	 <p>FIN (Finish)</p>
 <p>1</p>	<p>1st Insertion</p> 	 <p>PROGRAM</p>
 <p>END (Exit)</p>	 <p>0</p>	<p>Change Code128 to # Symbol ID : 1 character</p> 
<p>Change EAN8 to FF</p>  <p>PROGRAM</p>	 <p>0</p>	 <p>0</p>
<p>Symbol ID : 1 character</p> 	 <p>4</p>	 <p>0</p>
<p>Go to top of next column</p>	<p>Go to top of next column</p>	 <p>2</p>
		<p>Go to top left of next page</p>

 3	 4	 END (Exit)
 FIN (Finish)	 2	 PROGRAM
 PROGRAM	 5	Handshaking Protocol 
Change code39 to & Symbol ID : 1 character 	 FIN (Finish)	 1
 0	 END (Exit)	 END (Exit)
 5	 PROGRAM	
 2	UPC-E No Check Digit UPC Family Setting 	
 6	 C	
 FIN (Finish)	 END (Exit)	
 PROGRAM	 PROGRAM	
Change NW to % Symbol ID : 1 character 	Disable 2 of 5 Code 25 Setting 	
 0	 0	
Go to top of next column	Go to top of next column	