













<p>Enter/Exit Configuration Mode</p>  <p>3 9 9 9 9 9 9</p>		<p>Enable STX Prefix</p>  <p>3 1 1 6 6 1 5</p>
<p style="text-align: center;">↓</p>	<p>1 Stop Bit</p>  <p>3 1 1 6 0 1 4</p>	<p style="text-align: center;">↓</p>
<p>Recall Defaults</p>  <p>3 9 9 9 9 9 8</p>	<p style="text-align: center;">↓</p>	<p>Disable LF Suffix</p>  <p>3 1 1 6 6 0 2</p>
<p style="text-align: center;">↓</p>	<p>4800 BAUD Rate</p>  <p>3 4 1 5 8 4 0</p>	<p style="text-align: center;">↓</p>
<p>Odd Parity</p>  <p>3 3 1 6 0 0 5</p>	<p style="text-align: center;">↓</p>	<p>Convert UPC-A to EAN-13</p>  <p>3 1 0 7 5 1 4</p>
<p style="text-align: center;">↓</p>	<p>Enable RTS/CTS Handshaking</p>  <p>3 1 1 5 8 1 6</p>	<p style="text-align: center;">↓</p>
<p>* 7 Data Bits</p>  <p>3 1 1 6 0 0 3</p>	<p style="text-align: center;">↓</p>	<p>Enter/Exit Configuration Mode</p>  <p>3 9 9 9 9 9 9</p>
<p style="text-align: center;">↗</p>	<p>Enable UPC Prefix ID</p>  <p>3 1 1 6 6 1 7</p>	

